

## Specification

Model	YSSHSS2XXXXXXXXXX					
Dimensions	Half Slim, L54.0mm * W39.0mm * H4.5mm Error±0.15mm					
Interface	SATA 7+15PIN					
Protocol	SATA III (6Gb/s)- with backwards compatibility to SATA II (3Gb/s)					
Supported Systems	Windows 7,Windows 8,Windows 10,Windows Server 2012 R2,RHEL, CentOS,Ubuntu,Linux					
Capacity	8GB	16GB	32GB	64GB	128GB	256GB
NAND Flash	SLC	SLC	SLC	MLC	MLC	MLC
Sequential Read (MB/s)	170~200	220~300	480~520	450~500	450~500	500~550
Sequential Write (MB/s)	40~70	80~120	220~250	70~130	130~160	220~250
TBW	375TB	750TB	1500TB	185TB	375TB	750TB
4K Random read(IOPS)	20K(MAX)					
4K Random write(IOPS)	36K(MAX)					
Input voltage	DC 5V+/-5%					
Power consumption Idle	0.45W(MAX)					
Power consumption Active	2.06W(MAX)					
Data retention	10 years below 25 degree					
MTBF	2 million hours					
ECC	Hardware BCH ECC capable of correcting errors up to 66-bit/1KB					
Features	Power management/TRIM/S.M.A.R.T./NCQ/Wear-leveling					
Operating Temp.	-20°C ~ 75°C, -40°C ~ 85°C					
Storage Temp.	-55°C ~ 105°C					
Humidity	5-95%					



**Shenzhen KingSpec Electronics Technology Co., Ltd.**

Phone: 0755-26985321

URL: [www.yansen-ssd.com](http://www.yansen-ssd.com)

Office: 2001, Block C, Minzhi Joint Stock Commercial Center, North Station Community, Minzhi Street, Longhua District, Shenzhen, China, 518000