

Specification

Model	YSCF6-XXX				
Dimensions	CF Card, L42.8mm * W36.4mm * H3.3mm Error±0.5mm				
Interface	CF 50PIN				
Protocol	ATA/ATAPI-7				
Supported Systems	Windows 7,Windows 2003,Windows 2008,DOS,Linux,unix				
Capacity	8GB	16GB	32GB	64GB	128GB
NAND Flash	MLC	MLC	MLC	MLC	MLC
Sequential Read (MB/s)	40~50	45~55	55~65	60~70	70~80
Sequential Write (MB/s)	10~25	20~30	30~40	35~45	40~50
TBW	20TB	45TB	90TB	185TB	375TB
4K Random read(IOPS)	3120(Max)				
4K Random write(IOPS)	474(Max)				
Input voltage	DC 3.3V±5%				
Power consumption Idle	0.29W(Max)				
Power consumption Active	0.99W(Max)				
Data retention	10 years below 25 degree				
MTBF	2 million hours				
ECC	Hardware BCH ECC capable of correcting errors up to 72bit/1KB				
Features	System automatic bad block management				
Operating Temp.	0°C~70°C				
Storage Temp.	-40°C ~ 85°C				
Humidity	5-95%				



Shenzhen KingSpec Electronics Technology Co., Ltd.

Phone: 0755-26985321

URL: www.yansen-ssd.com

Office: 2001, Block C, Minzhi Joint Stock Commercial Center, North Station Community, Minzhi Street, Longhua District, Shenzhen, China, 518000