

## Specification

Model	YS44H6-XXXS		
Dimensions	IDE DOM, L48.0mm * W32.0mm * H4.0mm Error±0.5mm		
Interface	44PIN IDE DOM		
Protocol	ATA/ATAPI-7		
Supported Systems	Windows 7,Windows 2003,Windows 2008,DOS,Linux,unix		
Capacity	8GB	16GB	32GB
NAND Flash	SLC	SLC	SLC
Sequential Read (MB/s)	90~100	100~110	100~110
Sequential Write (MB/s)	60~75	70~85	80~95
TBW	375TB	750TB	1500TB
4K Random read(IOPS)	3000(Max)		
4K Random write(IOPS)	610(Max)		
Input voltage	DC 5V±5%		
Power consumption Idle	0.44W(Max)		
Power consumption Active	1.20W(Max)		
Data retention	10 years below 25 degree		
MTBF	2 million hours		
ECC	Hardware BCH ECC capable of correcting errors up to 72bit/1KB		
Features	Power management/TRIM/S.M.A.R.T./NCQ/Wear-leveling		
Operating Temp.	0°C~70°C		
Storage Temp.	-40°C ~ 85°C		
Humidity	5-95%		



**Shenzhen KingSpec Electronics Technology Co., Ltd.**

Phone: 0755-26985321

URL: [www.yansen-ssd.com](http://www.yansen-ssd.com)

Office: 2001, Block C, Minzhi Joint Stock Commercial Center, North Station Community,  
Minzhi Street, Longhua District, Shenzhen, China, 518000