

Specification						
Model	YSITXXX-P130 2280					
Dimensions	M.2 2280, L80.0mm * W22.0mm * H2.1mm Error±0.15mm					
Interface	M.2 B&M Key					
Protocol	SATA III (6Gb/s)- with backwards compatibility to SATA II (3Gb/s)					
Supported Systems	Windows 7,Windows 8,Windows 10,Windows Server 2012 R2,RHEL, CentOS,Ubuntu,Linux					
Capacity	32GB	64GB	128GB	256GB	512GB	1TB
NAND Flash	3D TLC	3D TLC	3D TLC	3D TLC	3D TLC	3D TLC
Sequential Read (MB/s)	280~320	300~350	510~560	510~560	510~560	510~560
Sequential Write (MB/s)	100~150	230~280	450~500	460~510	430~480	430~480
TBW	30TB	60TB	125TB	250TB	500TB	1000TB
4K Random read(IOPS)	69K(Max)					
4K Random write(IOPS)	81K(Max)					
Input voltage	DC 3.3V±5%					
Power consumption Idle	0.33W(Max)					
Power consumption Active	1.62W(Max)					
Data retention	10 years below 25 degree					
MTBF	2 million hours					
ECC	Low Density Parity Check(LDPC) ECC					
Features	Power management/TRIM/S.M.A.R.T./NCQ/Wear-leveling					
Operating Temp.	0°C~70°C					
Storage Temp.	-40°C ~ 85°C					
Humidity	5-95%					



Shenzhen KingSpec Electronics Technology Co., Ltd.

Phone: 0755-26985321

URL: www.yansen-ssd.com

Office: 2001, Block C, Minzhi Joint Stock Commercial Center, North Station Community, Minzhi Street, Longhua District, Shenzhen, China, 518000