

Specification						
Model	YSS25S2XXXXXXXXXX					
Dimensions	2.5 inch, L100.4mm * W70.0mm * H7.0mm Error±0.15mm					
Interface	SATA 7+15PIN					
Protocol	SATA III (6Gb/s)- with backwards compatibility to SATA II (3Gb/s)					
Supported Systems	Windows 7,Windows 8,Windows 10,Windows Server 2012 R2,RHEL, CentOS,Ubuntu,Linux					
Capacity	8GB	16GB	32GB	64GB	128GB	256GB
NAND Flash	SLC	SLC	SLC	MLC	MLC	MLC
Sequential Read (MB/s)	300~350	500~550	500~550	300~350	500~550	500~550
Sequential Write (MB/s)	150~200	250~300	350~400	150~200	250~300	350~400
TBW	375TB	750TB	1500TB	185TB	375TB	750TB
4K Random read(IOPS)	21700(MAX)					
4K Random write(IOPS)	21900(MAX)					
Input voltage	DC 5V+/-5%					
Power consumption Idle	0.66W(MAX)					
Power consumption Active	2.0W(MAX)					
Data retention	10 years below 25 degree					
MTBF	2 million hours					
ECC	Hardware BCH ECC capable of correcting errors up to 66-bit/1KB					
Features	Power management/TRIM/S.M.A.R.T./NCQ/Wear-leveling					
Operating Temp	-20°C ~ 75°C, -40°C ~ 85°C					
Storage Temp	-55°C ~ 105°C					
Humidity	5-95%					



Shenzhen KingSpec Electronics Technology Co., Ltd.

Phone: 0755-26985321

URL: www.yansen-ssd.com

Office: 2001, Block C, Minzhi Joint Stock Commercial Center, North Station Community, Minzhi Street, Longhua District, Shenzhen, China, 518000